

# ATESS EVA-44S4

ATESS EV AC Charging Station (three phase)



## LEADING - EDGE TECHNOLOGY

Three phase superfast AC charger for workplace or commercial use, single plug output

### Features



*Programmable charging mode*



*Compact and exquisite*



*Comprehensive protection*



*European Standard*



*Multiple communication modes*



*Flexible installation*

**Shenzhen Ateess Power Technology Co.,Ltd**

1st Floor of Building 3 at Sector B and 3rd Floor of Building 9,Henglong Industrial Park, No.4 Industrial Zone, Shuitian Community, Shiyan Street, Baoan District, Shenzhen

# Datasheet

## ATESS EVA-44S

### Input & Output

Input voltage	400V AC
Input frequency	50Hz
Output voltage	400V AC
Max. output power	44kW
Max. output current	63A
Charging interface type	IEC 62196-2, Type 2
Connection	Plug
Cable Length	5m

### Protection

Over voltage protection	Yes
Under voltage protection	Yes
Over load protection	Yes
Short circuit protection	Yes
Earth leakage protection	Yes
Over-temp protection	Yes
Lightning protection	Yes

### Function & Accessory

Ethernet/WIFI/4G	Yes/Yes/Opt
LCD	Yes
RCD	Type A + 6mA DC fault current protection (Equivalent to Type B)
Supported payment	RFID/QR(standard)
LED Indicator light	Yes
Emergency stop button	Yes
Intelligent power adjustment	Opt

### Working Environment

Protection degree	IP65
Operating temperature	-20°C ~+50°C
Relative humidity	5%-95% non-condensing
Maximum altitude	2000m
Cooling	Natural air cooling
Standby power consumption	<8W

### Mechanical

Dimension (W/H/D)	295/466/189mm
Weight	<16KG

### Mounting Accessories

Wall-mounting bracket/Ground-mounting pole	Yes/Opt
Certificate	CE